# IDEAL LOGIC+ 30 BOILER INTERNAL

MANUFACTURED BY:



The Logic+ 30 Condensing System Boiler provides excellent energy saving, and performs quietly in your home.

- · Made in the UK
- 1:5 Modulation rate
- · Built in Frost Protection
- · Large backlit LCD display
- · Aluminium Silicon Heat Exchanger
- · Light weight and compact design
- · Quiet operation
- · User friendly control panel

# Bendigo Hydronic Heating

**PHONE** 0418 128 584

sales@bendigohydronicheating.com.au



## **MAGNA CLEAN FILTER**



# **WATER TREATMENT**



#### **MODELS**

Logic+ 30kW System

#### **MEASUREMENTS**

700 (H) x 395 (W) x 278 (D) mm

## **BENDIGO HYDRONIC HEATING**

Servicing the Bendigo and surrounds, we have over 20 years experience designing, installing and servicing hydronic heating systems.

We have the knowledge, dedication and expertise to carry out any job with professionalism and attention to detail.

**PHONE** 0418 128 584

sales@bendigohydronicheating.com.au



Part of the Nissl Eichert Group

# **IDEAL LOGIC+ 30 SYSTEM BOILER INTERNAL**

Technical Information



General Data		30 System	
Gas Supply - NG/LPG		1.13kPa / 2.75kPa	
Gas Supply Connection		1/2"	
Flow Connection		3/4"	
Return Connection		3/4"	
Flue Terminal Diameter mm		100	
CO2 Content (± 0.7) NG/LPG	Max. CH	8.9%/10.7%	
	Min. CH	8.7%/10.4%	
Maximum Working Pressure (Sealed Systems)	kPa	250	
Electrical Supply		230 V ~ 50 Hz	
Power Consumption	W	100	
Min. thermostat cable size		1mm twin active	
Water Content	Litre	1.2	
Height	mm	700	
Width	mm	395	
Depth	mm	278	
Packaged Weight	kg	31.5	
Installation Weight	kg	26.1	
Performance Data		Min	Max
Boiler output - Mean 70°C	kW	6.1	30.3
Boiler output - Mean 40°C	kW	6.4	31.0
Gas Consumption	MJ/h	23.01	119.41
Boiler Efficiency	%	91.1	

